



N-Channel 40V (D-S) Power MOSFET

Features

- 100% Avalanche Tested
- Extremely Low Losses with Low FOM $R_{ds(on)} \cdot Q_g$
- RoHS Compliant, Halogen Free, Pb-Free
- AEC-Q101 Qualified
- MSL 1



LFPAK5060D



Applications

- Automotive systems
- Motors, lamps and solenoid control
- Ultra high performance power switching

Absolute Maximum Ratings ($T_J=25^\circ\text{C}$ unless otherwise noted, Single-side)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	40	V
Gate-Source Voltage	V_{GS}	± 20	V
Drain Current, Continuous $V_{GS}=10\text{V}$	I_D	$T_C=25^\circ\text{C}$	67
		$T_C=100^\circ\text{C}$	47
Drain Current, Pulsed (Note 1)	I_{DM}	268	A
Single Avalanche Energy (Note 2)	E_{AS}	180	mJ
Power Dissipation	P_D	$T_C=25^\circ\text{C}$	68
		$T_C=100^\circ\text{C}$	34
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 to +175	$^\circ\text{C}$

Note 1: Single Pulse; $t_p \leq 1\mu\text{s}$.

Note 2: $V_{DD} = 20\text{V}$, $V_{GS} = 10\text{V}$, $L = 0.5\text{mH}$, $R_G = 25\Omega$, starting $T_J = 25^\circ\text{C}$.

Thermal Characteristics (Single-side active)

Parameter	Symbol	Max.	Unit
Thermal Resistance Junction to Case	R_{thJC}	2.2	$^\circ\text{C/W}$
Thermal Resistance Junction to Ambient (Note 3)	R_{thJA}	62.5	$^\circ\text{C/W}$

Note 3: Device mounted on 1 square inch FR4 PCB board, with 2oz single-sided copper, in a 25°C still air environment.

Electrical Characteristics (T_J =25°C unless otherwise noted)







Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} =0V, I _D =250μA	40	--	--	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =40V, V _{GS} =0V	--	--	1	uA
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _{DS} =250uA	2	2.7	4	V
Gate Leakage Current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V	--	--	±100	nA
Drain-Source On-state Resistance (Note 4)	R _{DS(on)}	V _{GS} =10V, I _D =20A	--	5.6	6.8	mΩ
Total Gate Charge	Q _g	V _{GS(off)} =0V, V _{GS(on)} =10V, V _{DD} =32V, I _D =20A	--	35	--	nC
Gate-Source Charge	Q _{gs}		--	7.5	--	
Gate-Drain Charge	Q _{gd}		--	11	--	
Turn-on Delay Time	t _{d(on)}	V _{GS} =10V, V _{DD} =32V, I _D =20A, R _G =5Ω	--	6.3	--	ns
Turn-on Rise Time	t _r		--	24.3	--	
Turn-off Delay Time	t _{d(off)}		--	39.3	--	
Turn-off Fall Time	t _f		--	25.5	--	
Gate Resistance	R _g	V _{GS} =0V, f=1MHz, open drain	--	3.0	--	Ω
Input Capacitance	C _{iss}	V _{GS} =0V, V _{DS} =40V, f=1MHz	--	2200	--	pF
Output Capacitance	C _{oss}		--	231	--	
Reverse Transfer Capacitance	C _{rss}		--	115	--	

Reverse Diode Characteristics (T_J =25°C unless otherwise noted)

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Forward Current, Continuous	I _{SD}	T _C =25°C	--	--	49	A
Diode Forward Voltage (Note 4)	V _{SD}	I _F =20A, V _{GS} =0V	--	--	1.2	V
Reverse Recovery Time	T _{rr}	V _R =20V, I _F =20A, di/dt=100 A/μs	--	21	--	ns
Reverse Recovery Charge	Q _{rr}		--	14	--	nC

Note 4: Pulse test; pulse width ≤ 380μs, duty cycle ≤ 1%.

Typical Characteristics Curves (T_J = 25°C unless otherwise noted)



Typical Characteristics Curves (T_J = 25°C unless otherwise noted)

Fig. 7 - Capacitance




Fig. 8 - Gate Charge




Fig. 9 - Forward Characteristic




Fig. 10 - Safe Operating Area





Fig.11 - Normalized Transient Thermal Impedance, Junction-Case



Typical Characteristics Curves ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Fig. 12 - Power Derating






Fig. 13 - Drain Current Derating




Package Outline Dimensions (Unit: millimeters)

LFPAK5060D



LFPAK5060D							
	Min.	Nom.	Max.		Min.	Nom.	Max.
A	0.980	1.030	1.080	E	4.950	5.100	5.300
A1	-	0.050	-	E1	1.300	1.450	1.600
A2	0.000	-	0.100	E2	-	0.700	0.850
A3	-	0.254	-	e	-	1.270	-
b	0.350	0.400	0.500	L	0.800	1.010	1.300
b1	4.10	4.210	4.400	L1	0.300	0.510	0.750
c	0.190	0.200	0.250	Lp		0.610	
c1	0.240	0.254	0.300	H	5.900	6.000	6.200
D	4.450	4.590	4.700	Z	-	7°	-
D1	-	4.298	4.800	Z1	0°	-	8°
D2	-	3.450	-	-	-	-	-

Marking Outline



Part Name: AGMN06804DR

1. Logo Mark: 
2. P/N Mark: 06804DR
3. Date Code: AXXXX
4. Pin 1#: ○

Revision History

Version	Date	Major Changes
Rev.A	2024.06.18	Official Release

Disclaimers

These materials are intended as a reference to assist our customers in the selection of the Suzhou Good-Ark product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Suzhou Good-Ark Electronics Co., Ltd. or a third party.

Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.

All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Suzhou Good-Ark Electronics Co., Ltd. without notice due to product improvements or other reasons. It is therefore recommended that customers contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized Suzhou Good-Ark Electronics Co., Ltd. for the latest product information before purchasing a product listed herein. The information described here may contain technical inaccuracies or typographical errors. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors. Please also pay attention to information published by Suzhou Good-Ark Electronics Co., Ltd. by various means, including our website home page.

(<http://www.goodark.com>)

When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.

The prior written approval of Suzhou Good-Ark Electronics Co., Ltd. is necessary to reprint or reproduce in whole or in part these materials.

Please contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized distributor for further details on these materials or the products contained herein.