


N-Channel 100V (D-S) Power MOSFET

Features


- 100% Avalanche Tested
- Extremely Low Losses with Low FOM $R_{ds(on)} \cdot Q_g$
- Halogen Free, Pb-Free
- RoHS Compliant



TO-263AB (D²PAK)

Applications

- DC/DC
- Motors, lamps
- Power switching



Absolute Maximum Ratings ($T_J=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain Source Voltage	V_{DS}	100	V
Gate Source Voltage	V_{GS}	± 20	V
Drain Current, Continuous $V_{GS}=10\text{V}$ (Note 1)	I_D	$T_C=25^\circ\text{C}$	180
		$T_C=100^\circ\text{C}$	128
Drain Current, Pulsed (Note 2)	I_{DM}	720	A
Single Avalanche Energy	E_{AS}	781	mJ
Power Dissipation (Note 3)	P_D	300	W
Operating Junction/ Storage Temperature Range	T_J / T_{STG}	-55 to +175	$^\circ\text{C}$

Note 1: Calculated continuous current based on maximum allowable junction temperature.

Note 2: Repetitive rating; pulse width limited by max. junction temperature.

Thermal Characteristics

Parameter	Symbol	Max	Unit
Junction-to-case (Note 3)	$R_{\theta JC}$	0.5	$^\circ\text{C/W}$

Note 3: The power dissipation P_D is based on max. junction temperature, using junction-to-case thermal resistance.

Electrical Characteristics ($T_J = 25^\circ\text{C}$ unless otherwise noted)						
Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	100	--	--	V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=100V, V_{GS}=0V$	--	--	1	μA
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{DS}=V_{GS}, I_{DS}=250\mu A$	2	--	4	V
Gate Leakage Current	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$	--	--	± 100	nA
Drain-Source On-state Resistance	$R_{DS(on)}$	$V_{GS}=10V, I_D=50A$	--	2.5	3	m Ω
Total Gate Charge	Q_g	$V_{GS}=10V, V_{DS}=50V, I_D=100A$	--	105	--	nC
Gate Source Charge	Q_{gs}		--	40	--	
Gate Drain Charge	Q_{gd}		--	28	--	
Turn-on Delay Time	$t_{d(on)}$	$V_{GS}=10V, V_{DS}=50V, R_L=1\Omega, R_{GEN}=2.2\Omega$	--	39.2	--	ns
Turn-on Rise Time	t_r		--	14.8	--	
Turn-off Delay Time	$t_{d(off)}$		--	50	--	
Turn-off Fall Time	t_f		--	15.6	--	
Input Capacitance	C_{iss}	$V_{GS}=0V, V_{DS}=100V, f=100kHz$	--	6174	--	pF
Output Capacitance	C_{oss}		--	2600	--	
Reverse Transfer Capacitance	C_{rss}		--	73	--	

Reverse Diode Characteristics ($T_J = 25^\circ\text{C}$ unless otherwise noted)						
Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Continuous Source Current (Body Diode)	I_S	$T_C=25^\circ\text{C}$	--	--	180	A
Pulsed Source Current (Body Diode)	I_{SM}		--	--	720	
Diode Forward Voltage	V_{SD}	$I_S=50A, V_{GS}=0V$	--	--	1.2	V
Reverse Recovery Time	T_{rr}	$I_F = I_S, di/dt = 100 A/\mu s$	--	75	--	ns
Reverse Recovery Charge	Q_{rr}		--	185	--	nC

Typical Characteristics Curves ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Fig.1 - Typical Output Characteristics




Fig.2 - Drain-to-Source Breakdown Voltage vs. Junction Temperature




Fig.3 - RDS(on) vs. Junction Temperature




Fig.4 - Vth vs. Junction Temperature




Fig.5 - Capacitance





Fig.6 - Gate Charge



Typical Characteristics Curves ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Fig.7 - Transfer Characteristics






Fig.8 - Power Dissipation



Package Outline Dimensions (Unit: millimeters)


TO-263

Option 1




SYMBOL	MIN	NOM	MAX
A	4.35	4.47	4.60
A1	0.09	0.10	0.11
A2	2.30	2.40	2.50
b	0.70	0.80	1.00
b2	1.25	1.36	1.38
C	0.45	0.50	0.55
C1	1.29	1.30	1.31
D	9.10	9.20	9.30
D1	7.90	8.00	8.10
E	9.85	10.00	10.20
E1	7.90	8.00	8.10
II	15.30	15.50	15.70
e	-	2.54	-
L	2.34	2.54	2.74
L1	1.00	1.10	1.20
L2	1.30	1.40	1.50
R	0.24	0.25	0.26
θ	0°	4°	8°
θ_1	4°	7°	10°
θ_2	0°	3°	6°

Option 2




	MIN	NORMAL	MAX
A1	0.020	-	0.200
A2	4.470	4.570	4.670
A3	2.300	2.350	2.400
b1	0.750	-	0.850
b2	1.220	-	1.320
c1	0.500	-	0.550
c2	1.300	-	1.350
D	9.780	9.880	9.980
D1	9.880REF		
D2	7.400REF		
E	14.900	15.100	15.300
E1	9.100	9.200	9.300
E2	8.100REF		
e	2.540REF		
L	2.100	2.300	2.500
L2	1.025		1.375
L3	1.300	1.500	1.700
L4	2.400	2.500	2.600
θ1	3° TYPE		
θ2	3° TYPE		
θ3	7° TYPE		
θ4	7° TYPE		
θ	0 ~ 8°		

Marking Outline



Part Name: GMN03010W

1. Logo Mark: 
2. P/N Mark: 03010W
3. Date Code: XXXX

Disclaimers

These materials are intended as a reference to assist our customers in the selection of the Suzhou Good-Ark product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Suzhou Good-Ark Electronics Co., Ltd. or a third party.

Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.

All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Suzhou Good-Ark Electronics Co., Ltd. without notice due to product improvements or other reasons. It is therefore recommended that customers contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized Suzhou Good-Ark Electronics Co., Ltd. for the latest product information before purchasing a product listed herein. The information described here may contain technical inaccuracies or typographical errors. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors. Please also pay attention to information published by Suzhou Good-Ark Electronics Co., Ltd. by various means, including our website home page.

(<http://www.goodark.com>)

When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.

The prior written approval of Suzhou Good-Ark Electronics Co., Ltd. is necessary to reprint or reproduce in whole or in part these materials.

Please contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized distributor for further details on these materials or the products contained herein.